
Uncompromising simplicity and quality.

Always-reliable diagnosis, comfort, user-friendliness and fast capture times. Hy-Scan gives access to unrivalled digital technology and film-like ergonomics - all in one compact, affordable device.

MyRay, just right for you.



PERFECT FOR MultiROOM USE

Hy-Scan lets you optimise dental clinic work flows in MultiROOM. Thanks to the MultiROOM function, usable via Hy-Scan, the remote scanning system (connected to the SERVER) can be managed with a reservation made directly from the workstation alongside the patient (CLIENT PC). The patient is defined by a name and the colour of the surgery.

A simple APP - available in iCapture - lets you automatically save a series of remotely scanned images on the medical record of the patient, who is pre-selected in iRYS from the surgery from which you made the reservation. These images will be displayed immediately on the PC next to the patient.

	TECHNICAL DATA
Resolution (theoretical)	17 lp/mm
Image pixel size	30μ
Image grey levels	16 bit (65,536 grey levels)
Supported plate sizes	Size 0, 1, 2, 3
Plate size selection	Automatic
Read time	4 – 8 s
Plate Deletion	Automatic
Dimensions (H x L x P)	176 x 133 x 264 mm
Weight	4.5 kg
Power supply	110 - 240 V 50/60 Hz (24 Watts)
Connectivity	Direct to PC (USB)
Acquisition software (for PC)	iCapture with MultiROOM interface for third party software
Image management software (for PC)	iRYS (complies with ISDP@10003:2018 as per EN ISO/IEC17065:2012 certificate number 2019003109-1) and App iPad iRYS viewer (free)
Supported protocols	DICOM 3.0, TWAIN, VDDS
DICOM nodes	IHE compliant (Print; Storage Commitment, SR docu-ment; WorkList; MPPS; Query Retrieve)







Size 1 24 x 40 mm Pixels 792 x 1321 Dimensions in memory 2Mb



Size 2 31 x 41 mm Pixels 1024 x 1354 Dimensions in memory 3Mb



Size 3 27 x 54 mm Pixels 891 x 1783 Dimensions in memory 4Mb

MINIMUM SYSTEM REQUISITES

Supported operating systems: Microsoft® Windows® 7 (SP1) - 8 - 8.1 Professional (64 bit recommended);
Microsoft® Windows® 10 Professional 64 bit
Display settings: 1280 x 1024; 1344 x 768 or greater, 16 million colours

USB 2.0 or subsequent



www.my-ray.com

Plant - Via Bicocca, 14/c - 40026 Imola - Bo (Italy) tel. +39 0542 653441 - fax +39 0542 653555

Head Quarter - Cefla s.c. Via Selice Provinciale, 23/a - 40026 Imola - Bo (Italy) tel. +39 0542 653111 - fax +39 0542 653344

Cefla North America, Inc. - 6125 Harris Technology Blvd. Charlotte, NC 28269 - U.S.A. Toll Free: (+1) 800.416.3078 Fax: (+1) 704.631.4609



Hy-Scan

Phosphor Plate scanner





technology and tradition.

with the practicality and affordability of traditional film. The Hy-Scan phosphor plate

Outstanding digital imaging quality combined

scanner provides the perfect balance between

technology and tradition. Hy-Scan combines

produces high resolution intraoral images for

can import and digitize each image in rapid

the very best digital diagnostic technology with the advantages of traditional film plates. A compact, fast, simple device to use, which

High Definition.

Outstanding digital imaging quality combined with the


practicality and affordability of traditional film The Hy-Scan

phosphor plate scanner provides the perfect balance between

Hy-Scan • Phosphor Plate scanner

ULTRA-COMPACT AND ERGONOMIC

Featuring essential, compact design, the Hy-Scan scanner is perfect for any dental surgery. Extremely versatile, it can be installed both horizontally on the table or wall-mounted vertically using the special bracket.



USB CONNECTION


Fast, secure transfer of images to the PC next to the workstation or directly from the server in MultiROOM.

LED STATUS INDICATOR

Process always under control with instantaneous display of scanner status (ready / reading / image deletion / standby / etc.) thanks to the status indicator.

TOUCH-FREE

Fully automatic plate reading



sequence in just a few seconds, allowing them be displayed immediately on the PC or, via a special APP, on an iPad.

Easy, compact, reliable diagnostics.

- Essential, light, compact design
- High definition digital images
- Ergonomics and positioning comfort
- TOUCH-FREE user-friendliness
- Hard-wearing and reliable in MultiROOM



TOUCH-FREE ACQUISITION

User-friendliness and maximum workflow efficiency. Hy-Scan has a servo-assisted, fully automatic system that accepts and scans (TOUCH-FREE) the impressed plates, recognises the size, imports the image to the PC and deletes all the data from the plate so it is immediately ready for the next image capture.



FAST IMAGE DISPLAY

A high quality image can be imported in just a few seconds. Equipped with cutting-edge technology, Hy-Scan lets users view sharp images extremely quickly, leading to effective diagnosis and better communication with the patient.



iRYS - iPad CONNECTIVITY

Import data quickly thanks to the USB connection. Save and display captured images on the PC using the all-in-one iRYS diagnostic software with the convenient iPad viewer app and with any other control programme or image viewer equipped with a TWAIN or DICOM interface.

HIGH QUALITY IMAGES IN EVERY APPLICATION

Hy-Scan is the ideal tool for all clinical applications: endodontics, prostheses and implant surgery, periodontics and caries diagnosis. It reliably provides the very best high definition images with a resolution of 34 pixel/mm. The scanner is compatible with four sizes for the acquisition of paediatric (Size 0), periapical (Size 1), bitewing (Size 2) and long bitewing (Size 3) images with a pixel size of 30µm.











POSITIONING

AND ACQUISITION



RESERVATION

AND SCAN



DISPLAY AND

PROCES-SING





SHARING AND STORING

THE BEST WORKFLOW FOR EFFECTIVE DIAGNOSIS

Take X-rays with the desired plate size via user-friendly positioning and, if necessary, book the networked scanner. Capture high definition images by inserting the plates one at a time.

The images are then transferred to the local PC and/or sent to the client who booked it, ready to be consulted, shared and stored with iRYS software (or other viewer), printed and e-mailed.

